

# SKG-IKOB PRODUCTCERTIFICATE

## 441.633.01

Date of issue: 17-09-2020



### Certificate holder

FKS Okucia Okienne I Drzwoiwe Sp zoo  
Bronikowo, Morownicka 1c  
P64-030 Smigiel  
T: + 48 (0) 6551 88 024  
E: fks@home.pl  
I: www.fks.home.pl



### Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

#### narrow plate

delivered under logo / brand:

#### FKS

delivered under type- and / or article number:

**TYP 35 SKG xxxx PZ 72(KZ) , TYP 35 SKG xxxx PZ 92(KZ)**

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script.

ir. H.A.J. van Dartel  
Certification manager

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.  
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie  
Poppenbouwing 56  
4191 NZ Geldermalsen

Postbus 202  
4190 CE Geldermalsen

T 088-2440100  
[info@skgikob.nl](mailto:info@skgikob.nl)  
[www.skgikob.nl](http://www.skgikob.nl)

# SKG-IKOB PRODUCTCERTIFICATE

FKS Okucia Okienne I Drzwoiwe Sp zoo  
Number: 441.633.01

page 2 of 2

**1. PRODUCT**  
narrow plate

**PRODUCT TYPE**  
security furniture

---

## 2. TECHNICAL SPECIFICATION

Operating:	Mechanical operation
Construction:	1 set of an outside part and an inside part with mounting screws
System:	with OR without cylinder protection outside part with PC 72 OR PC 92 mm cylinder hole inside part with combination 72/92 mm hole various handles
Material:	outside part: extruded aluminium, anodised or coated; inside part: casted aluminium with ALU cover
Dimension:	outside part CH: 245x35x12 mm outside CP: 245x35x15 mm inside part: 245x33x8 mm
Fixing:	bolts: 3xM6 (10.9) in steel cams, h.o.h. 99,5/116,5 mm
Intended use:	wood, PVC, metal in combination with mortice locks on doors

---

## 3. DELIVERY

The delivery includes an installation instruction:  
SKG 35/26.10.2011

---

## 4. PERFORMANCES

A narrow plate according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this narrow plate is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this narrow plate is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).

---