SKG-IKOB PRODUCTCERTIFICATE 441.633.01

Date of issue: 13-10-2016





Certificate holder

FKS Okucia Okienne I Drzwoiwe Sp zoo Bronikowo, Morownicka 1c P64-030 Smigiel

T: +48 (0) 6551 88 024

E: fks@home.pl

I: www.fks.home.pl

Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

narrow plate

delivered under logo / brand:

FKS

delivered under type- and / or article number:

TYP 35 SKG xxxx PZ 92, TYP 35 SKG xxxx KZ 92

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual. This certificate contains 2 pages.

SKG-IKOB Certificatie Poppenbouwing 56 4191 NZ Geldermalsen

Postbus 202 4190 CE Geldermalsen

T 088-2440100 info@skgikob.nl www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

FKS Okucia Okienne I Drzwoiwe Sp zoo

Number: 441.633.01 page 2 of 2

1. PRODUCT MAIN GROUP narrow plate security furniture

2. TECHNICAL SPECIFICATION:

Construction: 1 set of an outside part and an inside part with mounting screws

Operating / System: with OR without cylinder protection; with PC 92 mm cylinder hole; various handles

Material: outside part: extruded aluminium, anodised or coated; inside part: casted aluminium with ALU cover

Dimension: outside part: 245x35x12 mm; outside CP: 245x35x15 mm inside part: 245x33x8 mm

Fixing: bolts: 3xM6 (10.9) in steel cams, h.o.h. 99,5/116,5 mm

Intended use: wood, PVC, metal

in combination with mortice locks on doors

3. DELIVERY

The delivery includes an installation instruction:

SKG 35/26.10.2011

4. PERFORMANCES

A narrow plate according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this narrow plate is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

• the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this narrow plate is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

• the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).